

TERRA KROME 1K Kit



User Instruction

Thank you for purchasing TERRA KROME 1K Kit.

Please read the following precautions and instructions carefully before use.

It is a 1K (1-component type) paint that is ideal for hobby painting. Drying process is quicker from the base color to the topcoat clear, and can be painted in a short amount of time compared to conventional two-component paint.

Contents: TERRA KROME 1K Kit

- ① TERRA KROME Micro Bottle 15ml
- ② Special KROME 1K Base Color Black Micro Bottle 15ml
- ③ Special KROME 1K Topcoat Clear Micro Bottle 15ml

1. Paint Special 1K-type KROME Base Color Black

For TERRA KROME, the shinier the surface of the base color, the more beautiful the plating becomes.

First, do the usual prep and paint the base color black avoiding dust and debris.

After painting the base color black, dry **at room temperature at 40~50°C about 2~3 hours, or 20~25°C with a household heater for about 24 hours or more.** Do not touch it during drying. If you touch it, fingerprints may come out from the place you touch after finishing with the topcoat clear after TERRA KROME paint.

2. Paint TERRA KROME

Put the TERRA KROME paint in the spray gun cup as it is. (Terra Krome main agent does not require dilution.)

Air blow without touching the dried Base Color black and paint TERRA KROME.

Please paint with an airbrush or spray gun about 4~5 times from semi-dry or half wet.

Each interval should be taken at least 5 minutes.

Immediately after painting, a blackish-brown color appears, but while drying, it gradually changes to plating color.

After applying TERRA KROME, dry at a **household heater at 40~50°C for about 2~3 hours, or 20~25°C at room temperature for about 24 hours or more.**

3. Paint Special 1K-type KROME Topcoat clear

Paint Topcoat clear on top of cured TERRA KROME.

First, spray super dry and mist state about 2~3 times.

Take the interval for about 5 minutes.

After painting super dry, dry again at **40~50°C about 2~3 hours, or 20~25°C at room temperature for about 24 hours or more.**

After drying, paint the Topcoat clear once semi-wet and finish to paint wet once.

Take intervals of about 5 minutes each.

Precaution:

- We recommend that you use this product within half a year after purchasing.
- Please use within 3 months after opening this product.
- When storing paints, please store it indoors. Especially in winter, if you are in an extremely cold area, be sure to store it indoors without leaving it outdoors.
- The finish of TERRA KROME application depends on humidity. Please avoid painting on rainy days and other humid days as much as possible.



Signal Inc., SHOW UP Division, 2-6-8 Aoshinke Mino Si Osaka, Japan 562-0024

<https://www.showup.jp/indexEg.html>